

## SPECIFICATION CHART LOW CARBON UNIFLEX STEEL STRAPPING

Size	Width mm	Thick mm	Break Load	UTS Kg/mm <sup>2</sup>	Bend	Elongation (150mmGL)	Winding	Yield (M/Kg)
1215	12.70	0.38	377	78.0	2	1.5% max	Mill	26.4
1218	12.70	0.46	450	77.0	2	1.5% max	Mill	21.8
1223	12.70	0.58	552	75.0	2	1.5% max	Mill	17.3
5815	15.88	0.38	470	78.0	2	1.5% max	Mill	21.1
5818	15.88	0.46	562	77.0	2	1.5% max	Mill	17.4
5820	15.88	0.51	623	77.0	2	1.5% max	Mill	15.7
5823	15.88	0.58	690	75.0	2	1.5% max	Mill	13.8
3415	19.05	0.38	564	78.0	2	1.5% max	Mill	17.6
3418	19.05	0.46	674	77.0	2	1.5% max	Mill	14.5
3420	19.05	0.51	728	75.0	2	1.5% max	Mill	13.2
3423	19.05	0.58	830	75.0	2	1.5% max	Mill	11.5
3425	19.05	0.64	915	75.0	2	1.5% max	Mill	10.3
1425	31.75	0.64	1485	73.0	2	1.5% max	Ribbon	6.2
1431	31.75	0.79	1830	73.0	2	1.5% max	Ribbon	5.1

Paint Colour:- Black, Brown, Green & Zinc Painted



### Tolerance

Width : +/- 0.127mm  
 Thick : +0.05mm,-0.025mm  
 Paint Thick : 5.0 Microns  
 Wax : Water Soluble  
 Coil ID/OD : 406/680 mm  
 Coil Weight : 45-50 Kgs Approx